

- (Ord. No. 8) cew South line N W 1/4 S Stone No. 116 S.  
 " " Red Oak 5 N 55 1/2 W 32 1/2 "  
 " " Beech 5 S 8 W 26 "  
 " " 9 West 1/2 mile cor. of Sec. 28 Stone No. 114 S.  
 " " "Original Bearings standing"  
 " " 10 cew S. W. 1/4 Sand Stone No. 116 S.  
 " " White Oak 40 S 29 E 23 1/2 Lks.  
 " " Do. 35 N 44 W 34 1/4 "  
 " " 11 cew E line S. W. 1/4 Sand Stone No. 116 S.  
 " " Elm 8 N 22 W 52 1/4 Lks.  
 " " Maple 20 S 14 E 5 1/2 Lks.  
 " " 12 cew S. E. 1/4 Sand Stone marked 1/16 S.  
 " " Beech 25 N 41 W 60 1/4 Lks.  
 " " Elm 20 S 30 E 27 "  
 " " 13 cew E line S. E. 1/4 Sand Stone marked 1/16 S.  
 " " W. Oak 30 S 66 W 51 Lks.  
 " " Hickory 30 S 43 E 84 3/4 "  
 " " 14 S. W. cor. of Sec. 28. Old tree & roots found  
 "(Remarks) of proper quality, course & distance for the  
 " " original set S Stone No. 28  
 " " Beech 20 S 88 E 28 1/2 Lks.  
 " " W. Oak 35 S 29 W 37 1/4 "  
 " " 15 cew South line of S W 1/4 S Stone No. 116 S.  
 " " Beech 20 N 78 E 26 1/2 Lks.  
 " " Ash 10 N 86 W 10 1/4 Lks.  
 " " 16 cew South line 28 Sand Stone No. 114 S.  
 " " Jack Oak 5 N 20 W 24 1/2 Lks.  
 " " Maple 5 N 48 E 16 1/4 Lks.  
 " " 17 cew <sup>South line of</sup> S. E. 1/4 No. 116 S.  
 " " Jack Oak 20 S 22 W 17 1/4 Lks.  
 " " Maple 10 N 56 1/2 E 25 1/4 "  
 " " 18 Set by running straight line from S. E. cor. of Sec. 27, to S. W.  
 cor. of Sec. 28 and at the point the line between Sec. 27  
 & 28 intersects set Sand Stone for S. E. cor. of Sec. 28  
 cornering with 27, 33, 34 Sand Stone No. 833, 34, 27, 28,  
 " " W. Oak 8 N 12 1/2 E 36 3/4 Lks.  
 " " Jack Oak - S - E 37 1/4 Lks.  
 (course of the J. Oak omitted)

See page 624