

Corners No. 8, 9 & 10 lines run & corners set by Geo. Goshorn C.S. commence 9 Nov. 1865. Chain carries record as Law directs  
Cord. No 8 cor. of West side N.E. 1/4 Sand Stone m 1/16

W. Oak 20 N 72 1/2 E 56 1/2 lbs.

B. Oak 15 S 27 W 38 1/2 lbs.

" " 9 center N.E. qr. Sand Stone m 1/16

Hickory 10 S 56 E 8 "

W. Oak 20. S 65 W 24 lbs.

" " 10 cor. N. line of N E 1/4 Sand Stone m 1/16

W. Oak 20 N 65 W 45 1/2 lbs

Beech 20 N 57 E 52 "

Further surveyed by McBinn surveyor August 26<sup>th</sup> 1869 cor. No 11 & 12 set

" " 11 set South of No 12 in half mile line Sand Stone m 1/16

J Oak 6 N 78 E 24

" 4 S 28 W 23

" " 12 Sand Stone set 25 Rod and 16 links East of No 9 cor. line

Elm 14 S 35 E 12

S Spruce 12 N 62 W 30

Further surveyed by J.B. Robertson surveyor of Clay Co. Ind. May 6<sup>th</sup> 1893. Cor. No 13 set by request of Jacob Baunmunk,

Cor 13. A Soft Sand Stone at the South East cor. of 31-11-6 and the S.W. cor of 37-11-6, marked S. 6 - two rods west from cor. to 386 10-6

Clint Porter 1965

151-139