

- Corner No 10 1/4 mile S of center
 " " " W. Walnut 5 S 12 W 127
 " " " W. Oak 24 N 48 E 90 1/2
- Corner No 11 N E corner of S. W. 1/4 of S E qn
 " " " J. Oak 10 S 10 W 9
 " " " B Oak 8 N 66 E 55 1/2
- Corner No 12 1/4 mile E of 1/2 on part of old T. line
 " " " Dogwood 4 N 2 E 11
 " " " Do 3 S 32 W 11
- Corner No 13 1/2 mile stake on T. line
 " " " B Walnut 15 North 102.
 " " " S Oak 8 N 80 1/2 W 172
- Corner No 14 1/4 mile W of 1/2 on part on T. line
 " " " Sugar 22 S 50 W 14 1/2
 " " " Beech 16 N 37 E 55

Sand Stones placed at all the corners and marked as the Law requires. Bearings taken at 5^o variation

Corner No 13 a new Stone deposited and other bearings taken by M. B. Crist Surveyor of Clay County 1869
 Cor No 13 a Sand Stone 30 in long N 1/4 S 86
 Red Oak 12 N 2 1/2 E 306 Me
 M. B. Crist S. C. C.

Corner No 13 a new Stone deposited and other bearings taken by M. B. Crist Surveyor of Clay County
 Feb. 1, 1869. Cor No 13 a Sand Stone 30 in long N 1/4 S 86
 Red Oak 12 N 2 1/2 E 306 Me
 M. B. Crist S. C. C.

Church lot in N. E. cor. of 20 rods Square and Cemetery in N. W. cor. of N. E. qn 8 by 20 rods Surveyed by Homer Hicks Surveyor of Clay County Indiana April 4th 1873
 Stones Nos. 1, 2, 3 and 4 Set and perpetuated.
 Homer Hicks, S. C. C.