

October 17th 1867 by consent and request of John F. Pell of Sec. 11, Benjamin F. Pell of Sec. 10 and Arthur Buttrick of sections 14 & 15 from one of the original bearings J. (P. J. Luther Surveyor & Co.) set and established the cor. for said sections above named described and witnessed as follows:

Cor. 13 S.W. cor. of Sec. 11 T13R6. a Flint stone 16 in NW S10, 11, 14 & 15 T13R6. 1 witness trees -
 a Beech 15-86 1 W 83. Sks.
 an Ash 6 S 7 1/2 E 101 "

Chain carriers sworn as the Law provides Recorded this October 19th 1867

P. J. Luther Surveyor,

By request of John F. Pell and Randolph Bowlin,
 I set corners 14 & 15 August the 6th 1868

No 14 a Sand Stone 16 marked 1/8 from which

" " a W. Oak 30 S 46 E 63 Sks.

No 15 a Stone 10 marked 1/10 from which

a R. Oak 14 S 6 E 23 "

a W. Oak 30 N 87 E 31 "

Witness my hand

P. J. Luther S, C, C.

Further surveyed May 21, 1882 by request of Sarah Squires
 Set Cor. 16 and found stone at No. 15 to establish line for the
 division of the E 1/2 of N. W 1/4 Sec. 11 T13N R6-W

No. 16 Set Iron pin. Witness iron pin 7.5 ft E of N. 16

Chainmen sworn as the law provides

R. L. McCormick S, C, C.