

- No. 9. S Stone 18 marked 1/8 S
- " " a Beech 18 N 32 E 35 C.
- " " a No 18 S 76 - 26 "
- No 10 a S Stone 18 marked 1/10 S.
- No " a Beech 10 N 50 E 48 3/4 S
- No 11 a S Stone marked 1/4 S.
- " " a Sugar 20 S 10° 30' E 24 1/2 "
- " " a S Stone marked W N 3° 15' E 32 1/2 "
- No 12 a S Stone 24 l. 1/8 S
- " " a S Stone 15 marked W N 7 W 50 1/4 "
- No 13 a S Stone Sec's 14, 15, 22, 23 NW corner, some old original bearings

Further Surveyed by D.S. Mauro Surveyor G. C.
 May 14 & 15 1880 John Williams and James
 Williams Chaimen. Sworn as law directs.

Corner 14	Sand Stone	No bearings
Corner 15	East of 14 ^{6 in} 9 E 1	Sandstone ^{14 in} No bearings
" 17	" " 6, 9, 81	" " 17 in. No bearings
" 18	" " 17 4 1/8	Niggerhead, 18 in. No bearings
" 19	" " 18 2 1/2	Sand Stone 18. "
" 20	" " 19 3 1/2	" " 18 "
" 21	" " 20 ^{40 1/2} 4 1/2	Niggerhead, 14 "
" 22	" " 21 2 1/8	" " 12 "
" 23	" " 15 4 1/8	Sand Stone 14 "
" 24	" " 23 2 1/2	" " 10 "
" 25	" " 24 3 1/2	" " 13 "
" 26	" " 25 4 0 1/2	" " 12 "
" 27	Black Oak, 16 North, 5 links	26 2 1/8 Sand Stone 11. No bearings

Found a stone at A between sections 14 & 23 when I was surveying Snell gravel road,
 John Williams a resident of VanBuren Township Clay County, State of Indiana appeared before me about 5 o'clock PM June 29, 1905 and took an oath that said stone had been moved.
 Subscribed & sworn before me this 29 day of June 1905
 A. H. Spears Deputy Surveyor C. C.