NORTH RANGE Sec 16, , WEST

Further Surveyed by Homer Hicks, Deputy County Surveyor May 11th 1881.
Survey made by request of Geroge W. Riddle and consent of the parties
interested- John Duncanan and Lenox K. Girton
Chainmen- both sworn -
Corner No. 10. a Sand Stone marked 1/16 S from which
" " " " " " a J. Oak 24. N 40 W. 14 lks.

Homer Hicks Deputy S. C. C.

Further surveyed by Thomas B. Robertson County Surveyor-
April 13" 1884 at request of James H. Morgan and consent of
parties interested. Chainmen and flagmen sworn
Corner No 11. a Fire Stone, White Oak 25. N. 23 W. 9 links
" " 12 Sand Stone 8 x 12. (No Witnesses taken)

Further surveyed by R. J. Maurer Deputy Surveyor
Clay County January 1st 1897. by request of Parties
interested.
Corner No 13. an Iron pin 23 in long with Square head
Set from Original bearings.
" " 13, an Iron pin 22 S 61 E. 40 1/2 lks-
" " " " " " " " 43 1/2 40 " 8 in South
East of Tame cherry Tree.
14 Sand Stone Center North Line of 40 A
15 Peg Iron 21 in Center between 10 and 11
16 Iron Bar 1 1/4 in Diameter 3 ft long Set 301 ft west of Cor 11
Double Elm 10 S 86 1/2 W 49 1/3 Lks

Further surveyed by Wm P Koehler Dep Surv. Clay Co Sep. 9-1913 at request of
Chas. Frost Parties consenting thereto James Elder chainman.
No 17. Iron buggy axle 30" x 1" x 1". Set 166.5 feet south and 256' East of Cor. #12.
" 18 " " " " " " . Set 215.5 " east of Cor #17.
19 Iron Pin 3/4" x 18" on north line of Vandalia R.R. right of way set
473.4 feet northeasterly along curve from an iron pin on quarter
section line

Further surveyed by Oscar J. Jenkins surveyor of Clay County May 18th 1926 at request
of Geo. Pell Parties consenting thereto.
No 20 Lime Stone 3" x 18" set 466' north of an iron pin at intersection of Penn R.R.
right of way and quarter section line
No 21 Lime stone set 427 feet west along right of way fence from quarter sect. line