

Corner no 5 S Stone nigger head 2 ft long 1 ft dia marked 44 x
 S and Stone 18 long 8 dia N 42 E 46 links

Corner no 6 Sand Stone 2 ft long 8 dia marked 46 x
 S Stone N 43 E 41 links

See Below

Corner no 7 S Stone 18 inch long 8 x 4 thick marked 46 x
 White Oak 10 Dia N 42 W 60 links

Corner no 8 S Stone 2 ft long 1 ft wide marked 44 x
 S Stone 8 dia N 49 E 60 links

Corner no 9 S Stone 18" long 8 marked 46 x
 S Stone 8 dia N 46 E 34 links

~~Corner 10 of Sec 22, 23 by consent of Bennett and others
 Sand Stone 2 1/4 in dia Bearings
 " " 1 1/2 in dia 30 links
 Witness S. G. S.~~

Also surveyed March 1/2 - 1915 by Wm. P. Kochler Deputy Surveyor
 Clay County. Interested Parties consenting to survey

10 Found a stone at 10.

11 " " " " 11.

12 A 3/4" square iron rod 30" long. 596.5 feet west of # 10.

Staked off line 12 to 11 parallel with 10 to 9.

Staked off line from 10 to 9. Corner # 12 not found But see below -

Kochler surveyed April 13^{and 14} 1915 by Wm. P. Kochler, Dep Surveyor Clay Co.

Cor # 2 Reset a Sandstone 1/4 way between # 10 & # 9 and 660 feet west of Cor. # 3 No Witness

Cor # 7 Reset a Sandstone 14" x 12" x 4" by subdividing from 3 to 1. No Witness.

Cor # 11 Several Small Stones set " " " " " "

Cor # 1 Reset a Niggerhead 4" x 8" x 13" Flat one side. No Witness. Set by subdividing from 12 to 13.

Cor # 12 See another section for Record of Corner. Put in Hollow Brick 4" x 3" x 15" over
 supposed stone from Witness

Further surveyed April 1st 1927 by Harvey Rardin Deputy Surveyor of Clay County,
 at request of Wm Barber. All parties given 10 day notice and present

Cor # 14 an iron pin 18" x 1" x 1" set 874.5' west of cor. # 10

Witness Persimmon tree 1' in dia, N 35° 00' W 17 feet

Cor # 15 buggy axle 3' x 1 1/2" x 1 1/2" set 874.5 west of cor. # 13

Witness Black Walnut 1 1/2 in dia. East 7 feet

New witness for cor # 13 Birch Tree 1' in dia. N 45° W 18'