

Cor. 9 1/4 mile E of S. W. cor. a S. S. 17 in marked 1/8
 " " " Cotton Wood 10 N 70 E 16 8/3 lbs.
 " " " In Prairie & no other tree near.
 Cor 10 Sev. of S. W. quarter a S. S. 14 in m. 1/8
 " " " a Jack Oak 7 S 4 1/2 W 7 8 lbs.
 " " " a do 3 N 20 W 14 3 1/2 "
 Cor. 11 1/4 mile N of S. W. cor. a Stone m. 1/8

In Prairie and no trees taken

Recorded by P. J. Luther

Corner 12. Sand Stone 22 in Surveyor Clay Co.
 " " " " 15 in North 30 inks.
 by consent of parties interested.

Corner 12 Reset by Thomas B. Robertson S.C.C.
 March 30th A.D. 1883. - Set in same place a
Yellow, or Reddish Flint - 8 x 13 inches.

Witnessed by a sand stone m. **R.B.** N 97 W. 52 Lbs.
 Said corner reset by request of Robert Bennett.

Recorded by Thomas B. Robertson Surveyor Clay Co.

Further surveyed by Fred C. Wilson, Dep. S.C.C., Aug. 29, 30 + 31
 1907, after ten days notice had been given all interested
 parties, the following corners were set

Cor 13 Sand stone 10" x 14" x 3" m x - no trees near

" 11 (Reset) Red S.S. 24" m x - Wit Elm 13 S 10 E 122 Ft.

" 10 (Reset) S.S. 23" m x - - Wit Nut Oak 8" S 1/2 W. 34 Ft

(Found Remains of old corner #10 and set new one in same place)