

NORTH RANGE Seven, 7, WEST

66  
22  
133

- Corner 9. a Sand Stone 15 in. 10 bearings
  - " " " Blue Lime Stone 15 in. South 50 links
  - " 10 East " " " " 10 bearings
  - " " " Stone pump South 15 in. 50 links
  - " 11 East Lime Stone 22 in. 10 bearings
  - " " " " " " 10. South 50 links
  - " 12 East Sand Stone 21 in. 10 bearings
  - " " " " " " 10. South 50 links
  - " 13 West Sand Stone 15 in. 10 bearings, 350 from 9
  - " 14 West Stone pump, 8 ft. 25 links
  - " 15 Blue Lime Stone 21. 10 bearings
  - " 16 " " " " " " 17 West 25 links
  - " 17 " " " " " " 19. 10 bearings
  - " " " " " " 13. West 25 links
  - " 16. " " " " " " 16 in. 10 bearings
  - " " " " " " 17 in. West 25 links
  - " 17 " " " " " " 18 in. 10 bearings
- D. S. Maurer & Co.

Surveyed by D. S. Maurer Deputy Surveyor, Clay Co. Mo.  
Dec. 12<sup>th</sup> 1896.

by consent of interested parties.  
Corner 1 an iron rod one in in diameter 3 ft. 2 in long. 3 3/4 ft.  
north of section corner 1.  
Iron pin at sec. corner.  
Corner 2 an iron pin 18 in long 3/4 in diameter.

Further Surveyed June 2-3-1910 by Geo. A. Shuler  
S. C. C. at request of Edw. Newton and interesting  
counseling R. Farnham - S. Ann chairman  
Corner 10. Lime Stone 3" x 5" x 10 - 907.5' N. + 744' N. and 104.5' E. of center of Sect.  
11. 19 Square Iron Rod 30' S. of E of Nat. Road.  
11. 20 " " " " " " " " " " " " 60 from cor. 19  
11. 21 Wooden stake 726' S. of cor. 20  
11. 22 " " " " " " " " " " " " 726' " " " " 19.

South side parallel with Nat. Road.  
Further Surveyed March 10-1917 - by Wm. P. Koehler, Surveyor Clay Co. at Request of Fred Hech - James Brann Chairman.  
11. 23 Niggerhead - recorded in small Field Book 1/4 mile - Wit. ss. North 27 links -  
11. 24 - 5' 16" Round Iron Pins 1" Diameter x 18" long - with square head on top. Set as shown -  
11. 25 and 26 are on S. property line of Vandalia R.R. Co. North and South lines are run by deflecting 91° 16' left  
from South section line.  
Wm. P. Koehler

See Record # 208