

Corner No 10 center of S.W. qr. stone

" " "

B. Oak 10 N 89 W 5-8 L.

" Cor 11 Reset by Hill peg head wit sand stone 6 in. North 40 links
Corner No 11 Section line N 1/4 mile corner a stone

B. Oak 8 N 1 1/2 W 86 L

Bottom road - S.W. 194 L.

Corners Nos. 12 + 13 Set by Homer Hicks S C C April 24-2 1874. by

request of Meredith Anderson & Caroline Modisett

J. J. Janness & Ambers Holland Chamber, Meredith Anderson & Marshal Modisett. Playmen

Corner No 12 Flint Stone 9 ins long 9.90 chns fr. E 1/2 in Cor + Cor Nos -

" " " " " " 2 white oak 2 1/2 S 47 W 78 links

" " " " " " a do 24 N 75 E 110 do

" 13 Flint Stone 15 - ins long at 10.03 3/4 chns fr N. E. cor of sec +

" " " " " " 10.03 3/4 fr N.W. cor of N. E. qtr N E qtr

" " " " " " 2 white oak 2 1/2 N 11 W. 8 links

" " " " " " a Sugar 27 S 48 W 35 do

Homer Hicks, Surveyor Clay County,

Further surveyed by D. S. Maurer, Surveyor Clay Co. and corners Reset April 22nd 1879 Fremont Stone & Marshal Modisett

Cor. No. 4 Aigger head (10) N. Corner

White Oak 12 in S 75 W 34 links.

Corner No. 3 Aigger head 15 in N. Corner

Black Oak 16 S 71 3/4 W 40 links.

D. S. Maurer Surveyor Clay Co.

Cor No 14 Lime Stone

Elm 6 1/2 S 46 1/2 W 114 Ls

Further surveyed by O. J. Jenkins, Surveyor of Clay County, Feb. 3, 1927. at

request of Donald Louderback and Merl Miller, to divide E 1/2 of N.W. 1/4

section 19 T. 12 N. of Range 7 W. into a 50 938 acre tracts

Cor # 15 an iron rod 3 1/2 long set 1076' North and 390' West of center of section

Cor. # 16 " " " " " " 5655' North of # 15

Cor. # 17 " " " " " " 991.0' south of N.W. corner of N.E. 1/4 of N.W. 1/4

of section