

NORTH RANGE *Seven (7)* , WEST

Corner No 9 @ Sand Stone 1/4 S,

" " " (Witness) Sand Stone crossed, N 59° W 50 lks,  
Stones, Sand Stone crossed, N 52° E 50 "

Corner No. 10 1/2 mile cor. on West side, Sand Stone 1/4 S,

" " " (Witness) S Stone crossed, N 14° E 30 lks  
Stones, Sand Stone crossed S 7° W 25 "

Corner No 11 @ Sand Stone marked 1/8 S

" " " (Witness) Sand Stone crossed " S 67° W 50 lks  
Stones, Sand Stone " N 63° 50 W 50 "

Corner No 12 (Original bearings found) Niggerhead 1/4 S

" " " (Witness) Niggerhead 6 in long & crop S 43° W 20 lks,  
Stones) " " 7 " S 80° E 20 "

Corner No 13 Bastard Lime Stone 1/8 S

" " " (Witness) Niggerhead crossed S 57° E 30 lks  
Stones, " " N 1° 30 E 30 "

Corner No 14 S.W. corner of the Sec. Basal Limestone S 95° 10 E 15 5/16

" " " (Witness) Niggerhead crossed N 49° E 25 lks  
Stones, Sand Stone " S 85° 30 W 30 lks

" " " *15* J. H. Davis g.l.c.,  
" " " 1386 Set by Thomas B. Robertson County Surveyor  
of Clay County Indiana May 8" 1884 at the request of  
Granville Brown.

" No. 15 Sand Stone 12 x 13 inches (In cleared land - no Bearings)

" " 16 Sand Stone No Bearings taken.

Further surveyed by J. L. Burns Co. Surveyor, Clay Co.,  
Indiana Sept. 16, 17 & 30 (89/2) with Joe Wimer and Andrew Clark <sup>Chairman</sup>  
and Granville Brown, flagman the first two days; and with W. H. Brenton and  
Milton Hoke flagmen and Harry Jenkins flagman on the 30"

Corner No. 5. Reset by Niggerhead, with the following witnesses

" " " Water Beech. 10 in, N 21 W. 54 lks.

" " " Beech 22 in, S. 69 W. 42 1/2 "

Corner No. 10. Reset with ~~Niggerhead~~. Blue Lime Stone

" " " Nigger Head S 33. E. 56 3/4 "

" " " Hickory 8 in, N 64. W. 58 1/4 "

Corner No. 17. Sand Stone Mt. Midway between 5 & 6,

" " " " " S 00 1/2 lks.

" " " " " E 24 "

Corner No. 18. Nigger Head. S. Stone. N. 33 1/2 lks.

" " " " " S. 41 "

Witnesses taken with ...