

NORTH RANGE Section (7) WEST

Corner No 10 "Sand Stone" 1/8 S.
 " " " } Witness } Sand Stone N 33° W 31 1/4 Lks
 " " " } Stones } Sand Stone S 82° E 30 "
 Corner No 11 Middle of S. E 1/4 Sand Stone 1/8 S.
 " " " } Witness } Sand Stone N 32° E. 31 Lks
 " " " } Stones } Sand Stone N 74° E 20 "
 Corner No 12 "Niggerhead" 1/8 S.
 " " " } Witness } "Niggerhead" N 25° W 34 Lks
 " " " } Stones } " " S 32° 30' W 40 "
 Corner No 13 Middle of S. E 1/4 "Niggerhead" 1/8 S.
 " " " } Witness } "Niggerhead" N 56° W 32 Lks
 " " " } Stones } " " S 29° E 35 "
 Corner No 14 "Niggerhead" Lettered 1/8 S.
 " " " } Witness } "Niggerhead" N 21° E 10 Lks
 " " " } Stones } " " S 44° E 12 "
 John H. Davis, Secy

Further surveyed by O. J. Jenkins S. C. C. July 27 & 28, 1925 at request
 of Wm. Webster. Parties duly notified and present, Joe Stevenson and Ray Mason
 chainmen.

Cor. #5 found and set iron coupling pin on top

Witness S. Stone 6" x 6" x 6" on end S 31° 30' E 36.5 feet

" " 6" x 6" x 6" " " N 55° 00' E 28.6 "

Cor. #6 an iron pin 1 1/2" x 1 1/2" x 15" set equal distance between 547 in line

Witness Boulder 1' x 6" x 8" S 55° 30' W 26.25 feet

" 1' x 1' x 8" on end S. 55° 30' E. 26.85 feet

Cor. #7 found and set iron bar on top 3 1/2" x 1 1/2" also set wooden stake on top of iron
 bar. two small S. Stone along side of stake.

Witness

Cor. #13 a boulder 1' x 1' x 8" set 1317.20 S. of #6

Witness 4 x 6 x 6 boulder N 0° 00' E 25 feet

" 6 x 12 x 12 " N 90° 00' W 25 feet.

Cor. #14 Stone set equal distance between 5415

Witness