

Cor. No. 10 S.E. corner a sand stone 24 in S.S., 6, 7, 8 E. 10 R.G.

a Beech 24 S.S. & 20 lbs,

a Jack Oak 8 East - 36 "

Witness my hand March 25th 1867 - P. J. Luther, S.C. Co.

Further surveyed by Thomas B. Robertson Surveyor of Clay Co.

Indiana July 7th 1885 - by request of Jacob Baumunk & Wm

William A. Allen they being the only parties interested

Cor. 11 A Sand stone marked **A** set South 5° East 31.0525 chains
from the N.W. corner of the E. 1/2 of the N.E. quarter. (No. witnesses)

" 12. A Sand stone set on the line between corners 4 and 8 on
the west side of the old canal bank. (The stone is marked **B**)

" 13. a Sand stone marked **J** N. 28 N. 10 chains

Corner 9⁺¹⁴ was reset July 8th 1885 by request of Wm A

Allen from witness given, the stone is now marked

1/4 ES

Cor. 14 a Sand stone marked **I** set at middle of the
~~East~~ East line of the South East quarter.

Corners 11, 12 & 13 are

Cor 15 A Lime Stone 6x4x22 in

Lime Stone 4x6x24 in N 45° E 35' Links

" 16 A Lime Stone 30 in

A Sand Stone North 25° E

17 A Lime Stone 24 in

A Sand Stone South 25° E

Further surveyed by A. D. Spears Dep.
surveyor Clay Co May 24 & 25, 1905 after notice
was served on all interested parties.

Cor

H. Addy Chairman

John Luther "

Chairman sworn

Cor 18 Lime stone 18" x 10" x 4", set it 1980' West of ^{Cor #} 10

" 19 " " 16" x 11" x 5" " " 30 rods West and

200' N of Cor 18 an account of corner coming in River

Further surveyed by A. J. Jenkins Surveyor of Clay County Oct. 2, 1926 Corners set for Baumunk Cemetery

Cor. # 20 4x6" Boulder no witness

" # 21 4x6" Sand stone no witness