

- No 11 Mid. of S side of S.E. gr. "Iron Stutter" 24 in long from which
Beech 24 in E 9 lbs.
- No 12 Set 12 by running straight through the Sec. to the Original 1/2 Sec. E,
cor taking 1/4 distance and set a sand stone ^(marked 1/4 by stone) 2 feet long 1/6 from which
a Beech 10 in S 13 1/2 E 23 lbs.
a W. Oak 24 in S 76 W 18 lbs.
- No. 13. Sand Stone 18 in long
Red Oak 6 in N 19 3/4 W 33 lbs
- No 14 Sand Stone 18 in long 1/6 from which
Ash 10 in S 4 E. 20 lbs.
W. Oak 20 in N 21 W 25 lbs
- No. 15 S. Stone 18 in long 1/6
White Oak 20 in N 11 W 5 lbs.
- No 16 Stake. Original bearing tree a Maple,
- No 17 Cor Sec. a S Stone Lettered.
- No 18 a Stake from which
" Hickory Stump Original bearing
Elm 10 in S 41 W 20 lbs
Ash 15 in N 25 E 30 lbs.
- No 19 S Stone no bearing S.E. cor of Sec.
Bearings taken with same Var. of line.

Cor. No 4 set correct Sand Stone 6 in long from which
Red Oak 16 S 44 W 35 lbs
Cor " 6 Altered and set cent. Sand Stone 16 in long 1/6
Close by on W side of White Oak Stump 2 in
(These corners were set showing the proper place according
to the Original 1/2 m. corner South side)

Further Surveyed by Thomas B. Robertson Surveyor of Clay Co.
Indiana April 8th 1885. by consent of parties interested Henry
Harden & Jacob Hudson Chairmen. Corners 5, 20, 21, 22, 23
set

- No 5 Sand Stone - marked 76. No 20. 25 rods 21 3/4 Links South of Cor. 3
a Sand Stone marked +. No 21 Sand Stone marked + - 4 1/2
Rods West from No 20. No 22. a Sand Stone 2 1/2 lbs long with
notch on the South side 25 Rods 21 3/4 Links South from Cor. No 5.
No 23. Sand Stone marked + 4 1/2 Rods West from Cor. No 4.