

Cor. No, 11 90 rods 20 3/4 lbs E of No 9 Sand Stone
" " " Witness White Walnut 8 No 8 11 9 9 lbs,

" " 12 90 rods 20 3/4 lbs E of No 8 Sand Stone, No bearings
Recorded By P. F. Luther Surveyor
C. C. Ind

On the 31st day of May 1867 by request of John Cooperider sen.
"it ab." Interested. I surveyed and established the S. E. corner
of the Town of Middleberry which is situated in the
above named section; said corner is a sand stone 25 in
marked 31 with stone coal at bottom. Witnessed by
a Sand Stone 19 in NW. N 38° E 50 Links

P. F. Luther Sur. W. Lay Co.

Further surveyed by M. P. Bliss Feb 25-1871

and corners 13 14 & 15 - see by request of Eli Sprangler

Cor No 13 B. lime stone 12 in long East of N.W. corner S.W. S.E. qtr 38 lbs

" " 14 B lime stone } 4 in dia Birch 22 1/2 E 8 } said stone is set East from 12 1/2 - 5.00

" " 15 B lime stone 20 in long south of said N.W. cor 8.34

M. P. Bliss Surveyor

Further Surveyed by Wesley Stark Aug 8th 1871

Corners No 16 Sand Stone M x

Sand Stone 4 diam S 36 W 45 link

Corners 17 Sand Stone M x

Sand Stone 10 diam N 10 E 50 "

Corners 18 Sand Stone M x

Sand Stone 4 diam S 66 E 64

Corners 19 Sand Stone M x

Sand Stone 5 diam S 86 E 75 "

Corners 20 Sand Stone M x

Sand Stone 6 diam S 65 E 18 "

Wesley Stark Dept Survey

See Records No 2 Page 38

T. B. Robertson, S.C.C. Ind.

Further surveyed by Thomas B. Robertson Surveyor of Clay Co
April 28 1893 by request of Jimmie Cooperider and Jerome Collins
they being the parties interested.

Cor. Z A.B.S.S. No. T Set 3.80's chains south of ~~3~~ 3 and 7.54 ch
West ~~from~~ being the N.W. corner of the school house lot
in Middleberry - T. B. Robertson S.C.C. (See Records No 2 p 38)