

On account of the gravel road corners number 1 and 13 were removed and again replaced in their original position, Sept 17th 1902. as follows
 Corner No. 1. Bar iron 1 1/2" x 24" at corner, Witness Bar iron 1 1/2" x 26" South 25 lbs
 " No 13 T iron 42" long, Witness White oak 4" N. 18 1/2 W. 49 1/2 ft.
 " 20" S. 65 3/4 E. 74 3/4 ft.

State of Indiana, Clay County, ss:

I hereby certify that the above corners numbers one and thirteen were replaced in their original places,

Dated this 17th day of September 1902,

L. W. Wain,

County Surveyor.

Further Surveyed Aug 23-1915 by Wm P. Koehler, Deputy Surveyor, Clay County, preliminary to the construction of a Brick Pavement on order of County Commissioners.

Cor. # 9 Relocated and Reset at 1/2 between 17 and 5. A Granite Boulder 17" x 12" x 9" with Pointed Ends.

Wit. A Sycamore 30" S 13 1/4 W. 41.8 ft. Southwest Corner of Residence - S 87 1/4 E - 19.3 ft.

Cor. # 6 Relocated and Reset at 1/2 between 9 and 5. A sandstone 15" x 8" x 4".

Wit. An Oak 14" N 87 W. 31.4 ft Oak 12" S 84 3/4 E. 19.9 ft.

Cor. # 7 Recorded Elsewhere. New Witness: - SE Corner N. of P. Bldg. N.W. 1/4 3.75. N. Co. Raybould Stone S.W. 37.5 feet

1825
 Further Surveyed Aug. 26 & 27, by O. J. Jenkins Surveyor, Clay County, at request of Sidney Turner and Benjamin Raybould. Both parties present.

Set corners 18, 19 & 20

Set corner 18 midway between 17 & 9 in line on iron pin 24" long

" " 19 1379.25' west of " 18. an old gate hinge 1 1/2" x 24"

" " 20 1379.25' " " " 19 " a T iron 30" long